



www.cbsystems.co.nz



FA1-H

Multi-Biometric Identification Terminal

Dual Cameras
User-defined Function Keys
4.3" TFT Touch Screen
Backup Battery (Optional)

Email : sales@cbsystems.co.nz
Phone : +64 9 889 0055

SPECIFICATION

LCD Display	Language
4.3"TFT Touch Screen	Multi language, English, French, Spanish, Arabic, Turkish, Portuguese, Czech, Hebrew, Slavic, Vietnamese etc., for more than 40 languages can be selected
Speaker	
Voice prompt (language can be selected)	
Capacity	Environment
Face: 1200(1:N)	Operation temperature:0°C-45°C Operation humidity:20%-80%
Fingerprint: 2,000	Memory
Logs: 100,000	256M flash, 64 SDRAM
Verification	Power Supply
Verification speed (1:1) ≤ 0.5s	110/220 VAC-12VDC 3A
Identification speed (1:1) ≤ 1s	Package info.
Identification	Machine size:19.4(L)*16.5(W)*86(H)cm Unit packing:31*26*12cm
FRR ≤ 0.01% FAR ≤ 0.0001%	Carton packing:50*34*38cm Real weight:1.6kg Volume weight:2.0kg
Attendance status	Function support
Check in/out, break in/out, OT in/out	Scheduled bell; DLST; Self-inquiry; Workcode; SMS; T9 input; Multi-alarm; Photo ID
Communications	Customize Function
TCP/IP, RS232/485, USB Hostx2	Wifi; GPRS; Printer support; Webserver; Li-battery
Access control	
Built-in relay, Door Sensor, Wiegand out	
Cameras	
High Definition Infrared Cameras	

FA1-H Multi-Biometric Identification Terminal